



WYSE 3030 THIN CLIENT

Big performance



While small in size, this Windows Embedded Standard 7 (WES7) thin client packs plenty of punch. Powered by a dual core Intel Celeron processor, it's more than capable of driving a wide range of applications, including HD multimedia and rich graphics, to just about all of your task workers and knowledge workers. In fact, it offers over four times the processing power and twice the graphics rendering capability of its Wyse predecessor thin client.

Broad application support

This Intel-based x86 embedded thin client runs WES7 locally to support all of your Windows apps via virtual desktop connection, locally on the device, or via a VPN. So you can support your entire existing app mix while you move your people to virtual desktops.

Highly configurable

What truly sets this thin client apart from others is how well-connected it is. With a choice of five back panel networking and peripheral interface choices, you can support a broad mix of network connections and device attachments. It's the thin client that can be configured for your entire organization.

Outstanding reliability

With no moving parts and built to last, the Wyse Intel-based 3000 series thin client will offer many years of high-performance service, which keeps your people and your IT and finance teams happy.

WYSE 3030 THIN CLIENT SPECIFICATIONS

OPERATING SYSTEM	Windows Embedded Standard 7
CPU	Intel Celeron N2807 1.6 GHz dual core processor
GRAPHICS	Integrated Graphics
MEMORY	16GB Flash / 4GB RAM DDR3
I/O PERIPHERAL SUPPORT	1 x DVI-I port 1 x DVI-D port 1 x USB 3.1 port on the front(backwards-compatible with USB 2.0) 3 x USB 2.0 ports (1 front, 2 back) Optional serial port
RESOLUTION	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate Single and dual display: 1920 x 1200 at 32bpp
NETWORKING	10/100/1000 Gigabit Ethernet Optional dual band 802.11 a/b/g/n/ac wireless Optional SFP Module support for Fiber NIC network connectivity
AUDIO	Composite audio jack: 1/8-inch mini, 16-bit stereo / Internal mono speaker
MOUNTING OPTIONS	Vertical feet, standard Optional VESA mounting bracket for mounting to flat surfaces, such as walls Optional Ergotron mounting stand for mounting with Dell monitors
DEVICE SECURITY	Built-in Kensington security slot (cable sold separately)
POWER	Worldwide auto-sensing 100-240 VAC, 50/60 Hz 65W, 19V DC Energy Star V.5.2 Phase V external and EuPcompliant power adapter Consumes less than 6 watts (average)
DIMENSIONS	Without stand: 7.37 in x 1.15 in x 4.61 in (187mm x 29mm x 117mm) With stand: 7.78 in x 1.15 in x 4.61 in (197.5mm x 69mm x 117mm)
NET WEIGHT	5.3 lbs. (2.34 kg)
TEMPERATURE RANGE	Operating: 32°to 104°F (10°to 40°C) Storage: 14°to 140°F (-10°to 60°C)
HUMIDITY	20% to 80% condensing. 10% to 95% non-condensing
WARRANTY	Three-year hardware warranty
SUPPORT AND DEPLOYMENT	Complete services portfolio including Deployment Services, ProSupportand Accidental Damage service.
SAFETY CERTIFICATIONS	Ergonomics: German EKI-ITB 2000, ISO 9241-3/-8 Safety: cULus60950, TÜV-GS, EN 60950 RF Interference: FCC Class B, CE, VCCI, C-Tick Environmental: WEEE, RoHS Compliant

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

WYSE 3040 THIN CLIENT

Quad-core performance on a budget

The Wyse 3040 is industry's first entry-level Intel x86 quad-core thin client*. Equipped with twice the number of CPU cores, this cost-effective endpoint is capable of supporting light multitasking and basic productivity. The Wyse 3040 features hardened, optimized Wyse ThinLinux as well as virus-resistant Wyse ThinOS.

Remarkably compact, the Wyse 3040 is Dell's smallest and lightest thin client* and comes with flexible mounting options for space constrained environments. It is also the most power efficient thin client, within its class. It consumes less than 4 watts of energy and is adept at offering many years of efficient, secure and high-performance service.



Flexible connectivity

The Wyse 3040 can connect to a variety of virtual desktop brokers including Citrix XenDesktop and XenApp, VMware Horizon, and Microsoft RDS right out of the box. It offers great multimedia capabilities, and essential protocol and peripheral support including optional PCoIP that enables connection to Amazon WorkSpaces (AWS). The Wyse 3040 includes a range of connectivity options including two DisplayPort interfaces, four USB ports, one of which is USB 3.1, as well as wired and wireless network connections.

Easy to manage, highly scalable

The Wyse 3040 thin client is highly manageable through Wyse Device Manager (WDM) and Wyse Management Suite. Administration easily scales from just a few to tens of thousands of thin clients.

With Wyse thin clients, customers get a complete services portfolio including Deployment Services, ProSupport¹ and Accidental Damage Service², and end-to-end support throughout the product lifecycle.

* Based on Dell internal analysis, March 2017.

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

WYSE 3040 THIN CLIENT SPECIFICATIONS

OPERATING SYSTEM	Wyse ThinOS, Wyse ThinOS with PCoIP Wyse ThinLinux
CPU	Intel® Atom x5-Z8350 (Quad Core 1.44 GHz)
GRAPHICS	Built-in Graphics controller. Three independent frame buffers. DirectX 11.1 compatible, OpenGL 4.3, OpenCL 1.2, OpenGL ES 3.0
MEMORY³	2GB DDR3L 1600MHz, soldered down
STORAGE⁴	ThinOS: 8GB eMMC FLASH, soldered down ThinLinux: 16GB eMMC FLASH, soldered down
I/O PERIPHERAL SUPPORT	3 x USB 2.0 (1 front/ 2 rear) 1 x USB 3.1 Gen 1 (front) 1 x Audio-mic combo jack 2 x DisplayPort™ 1.2 1 x 1Gb/s RJ45
SECURITY	Built-in chassis security lock slot (cable sold separately)
NETWORKING	Integrated Realtek® Ethernet LAN 10Mb/100Mb/1Gb Copper RJ45, Optional Azurewave AW-CM389MA Dual band 802.11 a/b/g/n/ac wireless with Bluetooth 4.0, internal antenna's (coming soon) ⁶
MULTIMEDIA	3.5 mm Audio-mic combo jack
DISPLAY	Up to two WQXGA (2560x1600) resolution digital displays @ 60Hz
POWER	External 15 Watt AC Adapter with local Type Duck Head Power Cord. Worldwide auto-sensing 100-240 VAC, 50-60 Hz Power consumption: 3.3 watts (idle)
DIMENSIONS	Height 101.6 mm x Width 27.94 mm x Depth 101.6 mm
NET WEIGHT	0.24 kg (0.53 lbs.)
SHIPPING WEIGHT	1.47kg/ 3.24 lbs. (Americas and APJ) 0.80 kg/ 1.76 lbs. (EMEA)
TEMPERATURE RANGE	Operating: 32°to 104°F (10°to 40°C) Storage: 14°to 140°F (-10°to 60°C)
HUMIDITY	20% to 80% condensing. 10% to 95% non-condensing
WARRANTY	Three-year Limited Hardware Warranty ⁵
SUPPORT AND DEPLOYMENT	Complete services portfolio including Deployment Services, Optional Dell ProSupport for premium support from expert technicians and 24x7 availability ¹ and Accidental Damage Service ² .
ENVIRONMENTAL, ERGONOMIC, & REGULATORY STANDARDS	Environmental Standards (eco-labels): ENERGY STAR 6.1 qualified, EPEAT Registered ⁷ , WEEE, EU RoHS ⁸ . Please see your local representative or www.dell.com for specific details

1. Dell ProSupport availability and terms vary by region. See dell.com/servicecontracts/global.

2. Accidental Damage Service excludes theft, loss, and damage due to fire, flood or other acts of nature, or intentional damage. Customer must return damaged unit. Limit of 1 qualified incident per contract year. See dell.com/servicecontracts.

3. System memory may be used to support graphics, depending on system memory size and other factors.

4. Hard Drive capacity varies with preloaded material and will be less.

5. Limited Hardware Warranty available by writing Dell USA LP, Attn: Warranties One Dell Way, Round Rock, TX 78682 or See dell.com/warranty.

6. Offering and availability may vary by region. Some items available after product introduction.

7. Please refer to www.epeat.net for specific country registration rating and participation

8. For a complete listing of declarations and certifications, refer to the Dell Regulatory and Environmental Datasheet found in the Manuals section of Product Support information <http://www.dell.com/support/home/us/en/1>

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

WYSE 3040 SOFTWARE FEATURE

OS OPTION	ThinOS	ThinOS with PCoIP	ThinLinux
ENVIRONMENT: <ul style="list-style-type: none"> MICROSOFT CITRIX VMWARE 	RemoteFX (RDP 8.1) Citrix Receiver 4.0.x VMware (RDP)	RemoteFX (RDP 8.1) Citrix Receiver 4.0.x VMware (RDP & PCoIP)	RemoteFX (RDP 8.1) Citrix Receiver 13.5 VMware (RDP, PCoIP and Blast Extreme)
LOCAL BROWSER	N/A	N/A	Firefox Browser Chrome Browser
CERTIFICATIONS	CITRIX HDX READY, CITRIX HDX PREMIUM, CITRIX HDX 3D PRO	CITRIX HDX READY, CITRIX HDX PREMIUM, CITRIX HDX 3D PRO	coming soon

WYSE 3040 THIN CLIENT RECOMMENDED OPTIONS & ACCESSORIES

SOFTWARE MAINTENANCE	Wyse ThinOS software maintenance 1, 2 or 3-year option
MANAGEMENT SOFTWARE	Dell Wyse Device Manager Workgroup Dell Wyse Device Manager Enterprise Dell Wyse Management Suite
MONITORS	Dell 19 Monitor E1916H Dell 19 Monitor P1917S Dell 20 Monitor E2016H Dell 20 Monitor P2017H Dell 22 Monitor E2216H Dell 22 Monitor P2217H Dell 24 Monitor E2416H Dell 24 Monitor P2417H
DISPLAY ADAPTORS	DisplayPort to Single Link DVI (1920x1200) Adapter Dell DisplayPort to VGA Adapter
MOUNTING OPTIONS	Wyse 3040 mount (wall mount and behind the Monitor Mount for E-series Monitors) Wyse behind the Monitor Mount for P-series 2017 Monitors Dell Dual Monitor Stand Dell MSA14 Single Monitor Arm Stand
KEYBOARDS	Dell Multimedia Keyboard-KB216 (default configuration) Dell Wireless Keyboard KM636 Dell Smartcard Keyboard KB813
MOUSE	Dell MS116 Wired Mouse Black (default configuration)
AUDIO	Dell Pro Stereo Headset UC300
SECURITY	Dell Premium Keyed Lock Dell Combination Lock LC300

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
 1-800-438-9973
ccc_sales@dell.com

ESSENTIAL ACCESSORIES



Dell 24 Monitor P2417H (dual setup)



Wyse behind the monitor mount for P-series 2017 monitors (with 3040 mount)



Wyse 3040 mount (wall mount and E-series Monitors)



Dell Wireless Keyboard and Mouse KM636



Dell Pro Stereo Headset UC300 – Skype for Business

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

WYSE 5060 THIN CLIENT

High-powered thin client

The Wyse 5060 is a highly efficient thin client with excellent multimedia capabilities and essential peripheral support, delivering an excellent virtual desktop experience, with extreme ease of use & management. It incorporates a high performance AMD 2.4GHz quad core processor and supports dual 4K displays for graphics-rich applications. The Wyse 5060 offers robust connectivity options with 6 USB ports, two of which are USB3.0, wired and wireless network connections.

Enhanced security and user experience

The Wyse 5060 offers enhanced security with virus-resistant Wyse ThinOS operating system to minimize viruses, malware, and patching. It supports a variety of virtual desktop brokers including Citrix XenDesktop, VMware Horizon and Microsoft RDS, and meets a broad and diverse range of user, applications and operating requirements including optional PCoIP support that enables connection to Amazon WorkSpaces (AWS). With support for unified communications solutions like Skype for Business, the Wyse 5060 thin client delivers the flexibility, efficiency and security organizations require for their cloud environments.

Easy to manage, highly scalable

The Wyse 5060 thin client is easily managed through Wyse Device Manager (WDM), Wyse Management Suite and Microsoft's System Center Configuration Manager (SCCM). Administration scales from just a few to tens of thousands of thin clients. For enhanced security, optional Advanced Threat Protection in the form of Dell Threat Defense offers proactive malware protection on both virtual desktops and WES endpoints themselves, respectively.

With Wyse thin clients, customers get access to a complete services portfolio including Deployment Services, ProSupport and Accidental Damage service, and with Dell business partners, end-to-end support throughout the product lifecycle.



Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

WYSE 5060 THIN CLIENT SPECIFICATIONS

OPERATING SYSTEM	Wyse ThinOS (with optional PCoIP) Wyse ThinLinux Windows Embedded 7 Pro (64bit) Windows IoT 10 Enterprise downgrade to Windows Embedded 7 Pro (64bit)
CPU	2nd Generation AMD Embedded G-Series SoC (Quad Core 2.4 GHz)
MEMORY CONFIGURATIONS	ThinOS : 8GB / 16/ 32 GB Flash SATA/ 4GB RAM DDR3 ThinLinux : 8GB Flash SATA/ 4GB RAM DDR3 WES7P/Win10 IoT: 64 GB Flash SATA/ 4GB RAM DDR3 (up to 8GB RAM)
I/O PERIPHERAL SUPPORT	4 x USB 2.0 2 x USB 3.0 1 x universal headset jack Bluetooth 4.0 (only with WiFi) 1 x 1Gb/s RJ45 2 X DisplayPort 1.4 2 X Dual Band 802.11a/b/g/n/ac wireless antenna
SECURITY	Built-in Kensington Security Slot (cable sold separately)
NETWORKING	Optional 802.11 a/b/g/n/ac dual band, 10/100/1000Mbps Ethernet (RJ45)
AUDIO	Integrated Speakers Universal headset jack
RESOLUTION	Dual display up to 3840x2160 @ 30Hz or 2560x1600 @ 60Hz
POWER CONSUMPTION	Under 25 watts
TEMPERATURE RANGE	Operating: 32°to 104°F (10°to 40°C) Storage: 14°to 140°F (-10°to 60°C)
HUMIDITY	20% to 80% condensing. 10% to 95% non-condensing
DIMENSIONS	Height 170 mm (without stand) Width 40 mm Depth 185 mm
WEIGHT	0.93kg (2.05 lb.)
WARRANTY	Three-year limited hardware warranty with optional ProSupport
SUPPORT AND DEPLOYMENT	Complete services portfolio including Deployment Services, ProSupport and Accidental Damage service.

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

LATITUDE 3480 MOBILE THIN CLIENT

Security and centralized control for digital workspaces, in a mobile package

Designed to securely deliver virtual desktops to mobile users, the Latitude 3480 mobile thin client leverages the thoughtful design and user experience of the Latitude portfolio with durable, enterprise-class chassis designed to meet the demands of today's mobile worker. Built with a robust feature set including Intel dual core processors with integrated graphics for a rich multimedia experience. This new mobile thin client delivers great value with a 14" Full-HD display and robust connectivity with plenty of ports. With a sleek, portable design, this mobile thin client is easy to carry and let you work on-the-go.



Flexible connectivity

The Latitude 3480 mobile thin client supports a wide variety of virtual desktop brokers including Citrix XenDesktop and XenApp, VMware Horizon, and Microsoft RDS right out of the box and connects to a broad range of peripherals and desktop / application virtualization environments using a fast, rich Windows 10 IoT Enterprise experience.

Easy to manage, highly scalable

The Latitude 3480 mobile thin clients are easily manageable through Wyse Device Manager (WDM), Wyse Management Suite and Microsoft's System Center Configuration Manager (SCCM). Administration easily scales from just a few to tens of thousands of mobile thin clients.

For enhanced security, optional advanced threat protection in the form of Dell Threat Defense offers proactive malware protection.

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

LATITUDE 3480 MOBILE THIN CLIENT SPECIFICATIONS

OPERATING SYSTEM	Windows 10 IoT Enterprise, 64bit
CPU	7th Gen Intel® Core Processors, U Dual Core (Kaby Lake - 7th Generation Intel®) Intel® Celeron 3865U (Dual Core, 1.8GHz, 2MB SmartCache, 15W)
GRAPHICS	Intel® Integrated HD Graphics
MEMORY³	8GB DDR4 RAM 2400 MHz running at 2133 MHz; 2 slots supporting up to 16GB
STORAGE⁴	128GB or 256GB M.2 280 SSD Class 20
I/O PERIPHERAL SUPPORT	1 x HDMI 1.4 1 x VGA 1 x USB 2.0 2 x USB 3.1 Gen 1 (one with PowerShare) 1 x RJ-45 1 x Multi-media card reader (SD 3.0) 1 x Universal Jack
SECURITY AND MANAGEMENT	Built-in chassis Noble Wedge security lock slot (cable sold separately) TPM 2.0 FIPS 140-2 Certified, TCG Certified Optional Dell Threat Defense Wyse Device Manager Wyse Management Suite Support for Microsoft's System Center Configuration Manager (SCCM) Dell Command Monitor
NETWORKING⁹	10/100/1000Mbps Ethernet via RJ45 WiFi 802.11 a/b/g/n/ac dual band. Qualcomm QCA61x4A 802.11ac Dual Band (2x2) Wireless Adapter+ Bluetooth 4.1
MULTIMEDIA	Integrated HD video webcam (1.0 megapixel) Integrated High Quality Speakers Universal Headphone Jack Integrated digital single array microphone
DISPLAY	14.0" (16:9) Anti-Glare, FHD (1920x1080) WLED, 220 nits with Integrated HD webcam, Non-touch
INPUT	Single Pointing Keyboard, w/Precision compliant Clickpad Touchpad (no buttons)
DOCKING	USB 3.1 Gen 1 Docking Only (optional, sold separately)
BATTERY	42 Whr ExpressCharge Capable (Prismatic) 56 Whr ExpressCharge Capable (Prismatic)
POWER OPTIONS	E4 65W AC Adapter, 7.4mm
DIMENSIONS	Height: 0.92" (23.3 mm) x Width: 13.3" (337.4 mm) x Depth: 9.6" (244 mm)
NET WEIGHT	3.89 lbs (1.76Kg)
TEMPERATURE RANGE	Operating: 32°to 104°F (10°to 40°C) Storage: 14°to 140°F (-10°to 60°C)
HUMIDITY	20% to 80% condensing. 10% to 95% non-condensing
WARRANTY	Limited Hardware Warranty ⁵ Standard 1 year Mail-in Service after Remote Diagnosis ¹⁰ , optional 3 year hardware warranty extension and 1-5 year Dell ProSupport contracts available ¹⁰

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

SUPPORT AND DEPLOYMENT

Complete services portfolio including Deployment Services, Optional Dell ProSupport for premium support from expert technicians and 24x7 availability¹ and Accidental Damage Service².

ENVIRONMENTAL, ERGONOMIC, & REGULATORY STANDARDS

Environmental Standards (eco-labels): ENERGY STAR 6.1 qualified⁶, EPEAT Gold Registered⁷, WEEE, EU RoHS⁸. Please see your local representative or www.dell.com for specific details
No TAA configurations available

9. Dell ProSupport availability and terms vary by region. See dell.com/servicecontracts/global.
10. **Accidental Damage Service** excludes theft, loss, and damage due to fire, flood or other acts of nature, or intentional damage. Customer must return damaged unit. Limit of 1 qualified incident per contract year. See dell.com/servicecontracts.
11. **System memory** may be used to support graphics, depending on system memory size and other factors.
12. **Hard Drive** capacity varies with preloaded material and will be less.
13. **Limited Hardware Warranty** available by writing Dell USA LP, Attn: Warranties One Dell Way, Round Rock, TX 78682 or See dell.com/warranty.
14. Offering and availability may vary by region. Some items available after product introduction.
15. Please refer to www.epeat.net for specific country registration rating and participation
16. For a complete listing of declarations and certifications, refer to the Dell Regulatory and Environmental Datasheet found in the Manuals section of Product Support information <http://www.dell.com/support/home/us/en/1>
17. Wireless antenna available only at time of system purchase
18. Dell Services: Availability and terms of Dell Services vary by region. For more information, visit www.dell.com/servicedescriptions.

LATITUDE 3480 MOBILE THIN CLIENT RECOMMENDED OPTIONS & ACCESSORIES

SOFTWARE	Dell Threat Defense
MANAGEMENT SOFTWARE	Dell Wyse Device Manager Workgroup Dell Wyse Device Manager Enterprise Dell Wyse Management Suite
MONITORS	Dell 20 Monitor E2016H Dell 20 Monitor P2016H Dell 22 Monitor E2216H Dell 22 Monitor P2217H Dell Ultra Sharp 24 Monitors Dell 23 Monitor P2317H Dell 21.5" Medical Review Monitor Dell 24 Monitor P2417H
DISPLAY ADAPTORS	Dell HDMI to VGA adapter
DOCKING OPTIONS	Dell D1000 Dual Video USB3.0 Docking Station
KEYBOARDS	Dell USB Wired keyboard with Smartcard Reader - KB813 Dell Wireless Keyboard and Mouse Combo- KM636
MOUSE	Dell MS116 USB Wired Optical Mouse Dell Wireless Mouse - WM326
AUDIO	Dell Pro Stereo Headset - UC300 (Lync and Skype Certified) Jabra Evolve 65 MS wireless headset (Stereo) - Office Centric Dell Pro Stereo Headset - Skype for Business Dell USB SoundBar - AE515 - Skype for Business Dell 2.0 Speaker System (Entry) - AX210
ADDITIONAL POWER SUPPLY	Dell spare notebook adapter, power cord Dell Power Companion PW7015L
CARRYING CASE	Dell Professional Sleeves (14") Dell Premier Briefcase M (14")
SECURITY	Noble Wedge Lock – TZ04T Dell Privacy Filter 14"

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com

ESSENTIAL ACCESSORIES

Powerful accessories designed and tested for business users to achieve essential productivity on-the-go or at their desk

At The Desk



Dell 24 Monitor P2317H



Dell Entry USB 3.0 dock - D1000



Dell Privacy Filter 14"



Dell Wireless Keyboard and Mouse KM636



Dell Pro Stereo Headset UC300 – Skype for Business

On-The-Go



Dell Power Companion (1800 mAh) – PW7015L

Simultaneously power your mobile thin client and up to two smartphones, tablets or other USB-enabled devices while on the go.



Dell Professional Sleeve 14

Protect your Latitude 3480 where ever your busy day takes you. The professionally-stylish heather gray exterior is also water resistant to protect your mobile thin client from the weather.

Learn More: Visit www.dell.com/wyse

Ask a Dell expert:
<https://marketing.dell.com/t2d-wyse>

Dell cloud client-computing sales
1-800-438-9973
ccc_sales@dell.com